



- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 - ▲4. RATING: 50VDC @ 50mA
 5. OPERATING FORCE: 130 ± 50 gms
 6. TRAVEL: 0.5mm ±0.2
 7. CONTACT RESISTANCE: 100 MILLI OHMS MAX. (INITIAL)
 8. MECHANICAL/ELECTRICAL LIFE: 80,000 CYCLES MIN.
 9. SILVER CONTACTS
 10. OPERATING TEMPERATURE: -40° TO 85°C
 11. STORAGE TEMPERATURE: -55°C TO 85°C
 12. PACKAGING: TUBES, 60 PIECES PER TUBE
 13. ▲ DENOTES CRITICAL PARAMETER
 14. 2002/95/EC (ROHS) COMPLIANT



TITLE TL6110DF130QP

B	17788	ADDED TEMP. NOTES	10/17/07	BF
REV	PCR NO	DESCRIPTION	DATE	BY

SCALE	DATE	DR	DWG	REV
2:1	10/17/2007	BF	D351008	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED